


SPECIFICATIONS

Static Pressure/Temp: 360 PSI / -22°F to 250°F
Service: Chilled water, hot water, up to 50% Glycol, or contact factory for additional fluids.
Flow Optimizer: Glass Filled Polymer
Body Material: Forged Brass ASTM B283-06
End Connections: Brass – NPT, Sweat or BSP
Field Repairable Stem: Dual Teflon seals and EPDM O-ring
Stem Seals: EPDM O-Rings
Ball Valve: Nickel-plated brass ball
Ball Seals: Teflon Seals with EPDM O-Rings
Angle of Rotation: 0-90°
Installation: Valve can be installed in mixing or diverting installations.

DIMENSIONS & WEIGHTS (NOMINAL) (measured in inches and lbs unless noted)

SIZE	MODEL NO.	THROUGH Cv	A:LENGTH		B:HEIGHT		C:LENGTH		D:DEPTH (NOT SHOWN)	E: HANDLE	F:HEIGHT		G:HEIGHT		WEIGHT
			FNPT	SWT	FNPT	SWT	FNPT	SWT			FNPT	SWT			
1/2"	UR3A_	0.33, 0.59, 1.0, 2.4, 4.3, 8.0	3.5	2.8	3.4	3.4	7.0	6.5	3.0	2.0	9.5	9.4	2.4	2.3	1.6
3/4"	UR3B_	0.40, 0.66, 1.3, 2.4, 3.8, 11.0	2.8	3.0	3.4	3.4	6.5	6.5	3.0	2.0	8.9	9.4	2.0	2.3	1.6
1"	UR3C_	0.40, 0.65, 1.3, 2.3, 3.5, 10.0	3.8	4.3	3.4	3.4	7.3	7.1	3.0	2.0	9.6	9.9	2.8	2.8	1.6
		8.6, 22.3	3.0	3.5	3.9	3.4	6.8	7.1			9.9	9.9	2.6	2.6	2.3
		4.5, 14.9, 30.8	4.5	4.3	4.1	3.9	7.8	7.8			10.9	10.9	3.3	3.5	3.6
1-1/4"	UR3D_	4.1, 8.7, 19.4	3.0	4.3	3.9	3.9	6.8	7.5	3.0	2.0	9.9	10.9	2.5	3.5	3.3
		12.7, 26.8, 34.1	3.6	4.0	4.1	3.9	7.3	7.3			10.4	10.4	2.8	3.0	3.5
1-1/2"	UR3E_	4.0, 8.3, 13.4, 32.0	4.5	4.3	4.1	3.9	7.8	7.8	3.0	2.0	10.9	10.9	3.3	3.5	3.6
		23.5, 61.1	4.0	4.3	4.6	4.1	7.3	7.5			11.1	11.1	3.3	3.5	5.2
2"	UR3F_	23.9, 38.2, 56.7	4.0	5.3	4.6	4.1	7.3	8.0	3.0	2.0	11.1	11.6	3.3	3.8	5.2
		82.6, 108.5	5.0	5.3	5.9	5.1	7.8	8.0			12.4	12.6	3.8	4.3	8.5
2-1/2"	UR3G_	38.1, 74.1, 99.5	5.0	N/A ¹	5.9		7.8	N/A	3.0	2.0	12.4	N/A	3.8	N/A	9.1

MODEL NUMBER SELECTION



NOTES

¹ Sweat ends are not available on 2-1/2" valves.
 Replaces form F-4306

This specification © 2007 Griswold Controls

THROUGH Cv SELECTION AND FLOW RATE TABLE (GPM)

LINE SIZE	MODEL NO.	THROUGH Cv	FULL ² PORT	CLOSE OFF ³	FLOWRATE (GPM) @ DIFFERENTIAL PRESSURE (PSI)											
					2-Position HVAC Apps					HVAC Modulating Apps						
					Cv ⁴		1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	7.0	10.0
1/2"	UR3A	A=0.33		50 PSI	0.2	0.33	0.4	0.5	0.5	0.6	0.6	0.7	0.7	0.7	0.9	1.0
	UR3A	B=0.59			0.4	0.59	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.3	1.6	1.9
	UR3A	C=1.0			0.7	1.0	1.2	1.4	1.6	1.7	1.9	2.0	2.1	2.2	2.6	3.2
	UR3A	D=2.4			1.7	2.4	2.9	3.4	3.8	4.2	4.5	4.8	5.1	5.4	6.3	7.6
	UR3A	E=4.3			3.0	4.3	5.3	6.1	6.8	7.4	8.0	8.6	9.1	9.6	11.4	13.6
	UR3A	F=8.0			5.7	8.0	9.8	11.3	12.6	13.9	15.0	16.0	17.0	17.9	21.2	25.3
3/4"	UR3B	A=0.40		50 PSI	0.3	0.40	0.5	0.6	0.6	0.7	0.7	0.8	0.8	0.9	1.1	1.3
	UR3B	B=0.66			0.5	0.66	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.7	2.1
	UR3B	C=1.3			0.9	1.3	1.6	1.8	2.1	2.3	2.4	2.6	2.8	2.9	3.4	4.1
	UR3B	D=2.4			1.7	2.4	2.9	3.4	3.8	4.2	4.5	4.8	5.1	5.4	6.3	7.6
	UR3B	E=3.8			2.7	3.8	4.7	5.4	6.0	6.6	7.1	7.6	8.1	8.5	10.1	12.0
	UR3B	F=11.0	•		7.8	11.0	13.5	15.6	17.4	19.1	20.6	22.0	23.3	24.6	29.1	34.8
1"	UR3C	A=0.40		50 PSI	0.3	0.40	0.5	0.6	0.6	0.7	0.7	0.8	0.8	0.9	1.1	1.3
	UR3C	B=0.65			0.5	0.65	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.7	2.1
	UR3C	C=1.3			0.9	1.3	1.6	1.8	2.1	2.3	2.4	2.6	2.8	2.9	3.4	4.1
	UR3C	D=2.3			1.6	2.3	2.8	3.3	3.6	4.0	4.3	4.6	4.9	5.1	6.1	7.3
	UR3C	E=3.5			2.5	3.5	4.3	4.9	5.5	6.1	6.5	7.0	7.4	7.8	9.3	11.1
	UR3C	F=10.0			7.1	10.0	12.2	14.1	15.8	17.3	18.7	20.0	21.2	22.4	26.5	31.6
	UR3C	G=8.6			6.1	8.6	10.5	12.1	13.6	14.9	16.1	17.2	18.2	19.2	22.7	27.2
	UR3C	H=22.3			15.8	22.3	27.3	31.5	35.3	38.6	41.7	44.6	47.3	49.9	59.0	70.5
	UR3C	J=14.9			10.5	14.9	18.2	21.1	23.6	25.8	27.9	29.8	31.6	33.3	39.4	47.1
	UR3C	K=4.5			3.2	4.5	5.5	6.4	7.1	7.8	8.4	9.0	9.5	10.1	11.9	14.2
	UR3C	M=30.8			21.8	30.8	37.7	43.6	48.7	53.3	57.6	61.6	65.3	68.9	81.5	97.4
1-1/4"	UR3D	B=19.4	•	40 PSI	13.7	19.4	23.8	27.4	30.7	33.6	36.3	38.8	41.2	43.4	51.3	61.3
	UR3D	C=12.7			9.0	12.7	15.6	18.0	20.1	22.0	23.8	25.4	26.9	28.4	33.6	40.2
	UR3D	D=4.1			2.9	4.1	5.0	5.7	6.4	7.0	7.6	8.1	8.6	9.1	10.7	12.8
	UR3D	E=8.7			6.1	8.7	10.6	12.3	13.7	15.0	16.2	17.3	18.4	19.4	22.9	27.4
	UR3D	F=34.1	•		24.1	34.1	41.8	48.2	53.9	59.1	63.8	68.2	72.3	76.2	90.2	107.8
	UR3D	G=26.8			19.0	26.8	32.8	37.9	42.4	46.4	50.1	53.6	56.9	59.9	70.9	84.7
1-1/2"	UR3E	A=13.4		40 PSI	9.5	13.4	16.4	18.9	21.1	23.2	25.0	26.7	28.4	29.9	35.4	42.3
	UR3E	B=4.0			2.8	4.0	4.9	5.7	6.4	7.0	7.5	8.1	8.5	9.0	10.7	12.7
	UR3E	C=8.3			5.8	8.3	10.1	11.7	13.1	14.3	15.5	16.5	17.5	18.5	21.9	26.1
	UR3E	D=32.0	•		22.6	32.0	39.2	45.3	50.6	55.5	59.9	64.0	67.9	71.6	84.7	101.3
	UR3E	E=23.5			16.6	23.5	28.8	33.3	37.2	40.8	44.0	47.1	49.9	52.6	62.3	74.4
	UR3E	F=61.1			43.2	61.1	74.8	86.4	96.6	105.8	114.3	122.2	129.6	136.6	161.6	193.2
2"	UR3F	A=23.9		40 PSI	16.9	23.9	29.3	33.8	37.8	41.4	44.7	47.8	50.7	53.4	63.2	75.6
	UR3F	B=56.7			40.1	56.7	69.4	80.2	89.7	98.2	106.1	113.4	120.3	126.8	150.0	179.3
	UR3F	C=38.2			27.0	38.2	46.8	54.0	60.4	66.2	71.5	76.4	81.0	85.4	101.1	120.8
	UR3F	D=108.5			76.7	108.5	132.9	153.4	171.6	187.9	203	217	230	243	287	343
	UR3F	E=82.6			58.4	82.6	101.2	116.8	130.6	143.1	154.5	165.2	175.2	184.7	219	261
2-1/2"	UR3G	A=38.1		40 PSI	26.9	38.1	46.7	53.9	60.2	66.0	71.3	76.2	80.8	85.2	100.8	120.5
	UR3G	C=74.1			52.4	74.1	90.8	104.8	117.2	128.3	138.6	148.2	157.2	165.7	196.1	234
	UR3G	B=99.5	•		70.4	99.5	121.9	140.7	157.3	172.3	186.1	199.0	211	223	263	315

NOTES

- ² These valves are full port and do not have the Optimizer insert.
- ³ Close-Off Pressures measured with 35 in-lb. actuator. The "Close Off Pressure" is the maximum allowable pressure drop across the valve body when the valve is fully closed. (Do not use actuators with torques higher than 90 in-lbs)
- ⁴ The Cv is the gallons of water per minute (gpm) at 60°F that the valve will pass at 1 PSI pressure drop. Hence the 1.0 PSI pressure differential column in the table above is equivalent to the Cv value.

Replaces form F-4306


This specification © 2007 Griswold Controls

9/07
F-5396




PIPING CONFIGURATIONS

Our 3-Way ball allows the same 3-Way valve to be installed in either a mixing or diverting configuration without sacrificing any performance or Cv.



Mixing — fluid enters through two inlets (A, B) and exits through one outlet (AB)



Diverting — fluid enters through one inlet (AB) and exits through two outlets (A, B)

ACTUATOR MODEL NUMBER SELECTION

Griswold Controls Private Label	EMO-35F-24 EMO-35FV-24	EMO-35M-24 EMO-35MV-24	EMO-35F-24- 10S	EMO-70S-24SR
Torque of 35 in-lb	•	•	•	
Torque of 70 in-lb				•
Control Signal: On/Off	•		•	•
Control Signal: 3 Point	•			
Control Signal: Modulating 2–10 VDC		•		
Speed	150 sec	150 sec	8-10 sec	150 sec
Fail Safe (Spring Return)				•
Operating Power	4VA	4VA	6VA	8VA
Weight	1.5 pounds	1.5 pounds	2.2 pounds	4.2 pounds
Wiring Diagram				

Replaces form F-4306

This specification © 2007 Griswold Controls

Griswold Controls Private Label	GCDE131.1P	GCDE161.1P	GCMA121.1P	GCMA131.1P	GCMA161.1P
Torque of 44 in-lb	•	•			
Torque of 62 in-lb			•	•	•
Control Signal: On/Off			•		
Control Signal: 3 Point	•			•	
Control Signal: Modulating 0–10 VDC		•			•
Speed	90 sec	90 sec	90 sec	90 sec	90 sec
Fail Safe (Spring Return)			•	•	•
Operating Power	3.3 VA	3.3 VA	5 VA	5 VA	5 VA
Weight	1.1 pounds	1.1 pounds	3.0 pounds	3.0 pounds	3.0 pounds
Wiring Diagram	<p>Where 6 is CW and 7 is CCW</p>				

ADDITIONAL COMPATIBLE ACTUATORS:

- Belimo: LM24, LM24S, LF24, LF24S, LF120, LF120S, LF24-3, LF24-3S, LM24SR, LF24SR, LF24SRS
- ELODrive: BN-44C1U, BNP-44C1U, BS-26F1U, BSP-26F1U, BN-44P1U, BNP-44P1U, BS-26P1U, BSP-26P1
- Honeywell: ML6161D2006, ML6174D2009, ML7161A2008, ML7174A2001, ML6185A1000, ML6185C1008, ML8185A1008, ML8185C1006, ML7285A1007, ML7285C1005
- Johnson Controls: M9106-AGA2, M9106-AGC2, M9106-GGA2, M9106-GGC2, M9206-AGA2, M9206-AGC2, M9206-GGA2, M9206-GGC2
- KMC Controls: MEP-5072, MEP-5073, MEP-5372, MEP-5373
- Neptronic: BBT-24, BBT-1000, BBT-1060, BBT-1021, BBT-1080, BBTHV-1100, BBTHV-1160, BBTHV-1120, BBTHV-1180, BBM2000A, BBM2060A
- Siemens: GDE131.1P, GDE161.1P, GDE136.1P, GDE166.1P, GMA121.1P, GMA161.1P
- TAC: MF40-6083, MA40-7043, MA40-7043-501, MA40-7040, MA40-7040-501, MF40-7043, MF40-7043-501, MS40-7043, MS40-7043-501

Replaces form F-4306

This specification © 2007 Griswold Controls

2803 Barranca Parkway, Irvine, CA 92606
 (949) 559-6000 Fax (949) 559-6088
 www.GriswoldControls.com

9/07
 F-5396

